

TRASH PUMPS



TRASH PUMPS

Specifically designed pumps for heavy duty applications. Handles solids with ease and simple to open and clean. Standard roll cage protects pump and engine. Steel strainer for intake hose included. Available with either Briggs & Stratton Intek™ Pro or Honda engines.

56200 2" TRASH PUMPS

Features: 2" suction/discharge ports, 180 gpm/680 lpm, max solids up to 1",
6.5 hp. B & S engine.89 lbs. (41kg)
56201 Same as 56200 but with wheeled cart104 lbs. (47kg)

562000 Same as 56200 except with 5.5 hp. Honda engine.89 lbs. (41kg)
562001 Same as 562000 but with wheeled cart104 lbs. (47kg)

Accessories:

56250 2"x20' Suction Hose
56251 2"x25' Discharge Hose
56252 2" Cam Style Quick Connector Set
276270 Pump Repair Kit



56300 3" TRASH PUMPS

Features: 3" suction/discharge ports, 300 gpm/1140 lpm, max solids up to
1.25", 6.5 hp. B & S engine.98 lbs. (46kg)
56301 Same as 56300 but with wheeled cart113 lbs. (52kg)

563000 Same as 56300 except with 5.5 hp. Honda engine.98 lbs. (46kg)
563001 Same as 563000 but with wheeled cart113 lbs. (52kg)

Accessories:

56350 3"x15' Suction Hose
56351 3"x25' Discharge Hose
56353 3" Cam Style Quick Connector Set
276271 Pump Repair Kit

56310 3" MUDSUCKER DIAPHRAGM-STYLE TRASH PUMP

Features: 6.5 hp. B & S engine 3" female suction/discharge ports, 90 gpm / 340 lpm,
capable of pumping mud, slurry, sewage, thick liquids
and max solids up to 1 5/8".203 lbs. (93kg)

563100 3" MUDSUCKER DIAPHRAGM-STYLE TRASH PUMP

Features: Same as 56310 except with 5.5 hp. Honda engine.....203 lbs. (93kg)

Accessories:

56350 3"x15' Suction Hose
56351 3"x25' Discharge Hose



4" ENGINE DRIVEN TRASH PUMP

Designed for applications which require high flow and solids handling capability. Constructed of heavy-duty sand cast components with removable/replaceable cast iron volutes, impellers and wearplates. Easy front cleanout without disconnecting the hoses.

56400 13 hp. B & S Vanguard engine214 lbs. (97kg)
564000 13 hp. Honda OHV engine214 lbs. (97kg)

Features: • 4" suction/discharge ports • Low oil alert on engine
• 540 gpm/44 psi • Self priming up to 20 feet
• Up to 2" maximum solids handling

Accessories:

56451 4"x15' Suction Hose
56452 4"x25' Discharge Hose
56354 4" Cam Style Quick Connector Set



Diesel engines available – Special request