

WHEELER-REX PIPE TOOLS

HAND OPERATED SOIL PIPE COUPLING TORQUE WRENCH



“T-Handle” type torque wrench features a unique locking collar, which enables the wrench to be used as an untorqued snug-up or back-off tool or as a conventional torque wrench. Retracting the locking collar allows the tool to torque right (tightening), while ratcheting to the left. When proper torque value has been attained, an internal slip mechanism eliminates the ability to over-tighten.

Model No. 1967 “T” Torque Wrench for tightening 5/16” coupling nuts to 60 in. lbs.



Wheeler Manufacturing, Division of Rex International U.S.A., Inc.

P.O. Box 688, 3744 Jefferson Road, Ashtabula, Ohio 44005

Phone: 440-998-2788 Fax: 440-992-2925 Toll-Free: 1-800-321-7950 www.wheelerrex.com

WHEELER-REX PIPE TOOLS

POWERED NO-HUB COUPLING WRENCHES



Tighten or loosen No-Hub couplings in just seconds with the Wheeler-Rex No-Hub coupling wrenches. Designed for use with virtually any 3/8" reversible, electric drill, No-Hub coupling wrenches are easily chucked or un-chucked as any drill bit. These unique No-Hub wrenches feature an automatic clutch within the torque head to prevent over or under tightening. Recalibration can easily be done with a torque wrench.

Model No. 1964 "Fastite" for tightening 5/16" coupling nuts to 60-in. lbs.

Model No. 1965 "Fastite Plus" for tightening 3/8" coupling nuts to 80-in. lbs.



Wheeler Manufacturing, Division of Rex International U.S.A., Inc.

P.O. Box 688, 3744 Jefferson Road, Ashtabula, Ohio 44005

Phone: 440-998-2788 Fax: 440-992-2925 Toll-Free: 1-800-321-7950 www.wheelerrex.com